
# CHRYSO<sup>®</sup>MS IR 920 CHRYSO<sup>®</sup>MS IR 920



# **Modified Micro Silica Gel Additive**

# Features

CHRYSO®MS IR 920 is a modified micro silica gel including special polymer additives to enhance the fresh and hard concrete properties

CHRYSO®MS IR 920 is supplied as a grey gel ready to use in concrete mix design.

CHRYSO®MS IR 920 is chloride, bituminous and ammonia free.

# Benefits

• CHRYSO®MS IR 920 is especially recommended for concrete requiring high early age and long term strengths, whilst maintaining the workability.

• CHRYSO®MS IR 920 Improve dramatically the durability of concrete, by reducing permeability and enhancing strength at all ages, furthermore the concrete will be more resistant to chemicals attack.

• CHRYSO®MS IR 920 enhance the fresh concrete properties by reducing bleeding and mix tendency to segregation when poor aggregates are used.

• The usage of CHRYSO®MS IR 920, will make the concrete mix more cohesive which improve the pumpability.

• CHRYSO®MS IR 920 Improves the efficiency of cement in concrete, effectively reducing the quantity of cement required to achieve specified concrete properties

•The special formulation of CHRYSO®MS IR 920 will improve the workability of fresh concrete and slump retention, to certain extend, without the addition of a plasticizing admixture.

# Areas of Application

CHRYSO®MS IR 920 is recommended for all concrete mixes where low permeability and high concrete specifications are required.

- 1.All types of cement
- 2. Heavy prefabrication
- 3. High performance concrete, ultra high performance concrete
- 4. Pre-stressed concrete
- 5. Ready-mix concrete
- 6. Concrete of humid, plastic or fluid consistency
- 7. Self-levelling concrete
- 8. High strength concrete with high workability retention
- 9. Compatible with GGBS and Fly Ash.
- 10. durable concrete
- 11.Concrete with high resistance to chemicals





# CHRYSO®MS IR 920 CHRYSO®MS IR 920

# Description:

#### Characteristics:

CHRYSO®MS IR 920 is a chemically stable Gel.

1.Nature : Gel 2.Colour : Grey 3.Density :  $1.380 \pm 0.030$ 4.pH :  $6 \pm 2$ 5.Cl<sup>-</sup> ions content: nil

**CHRYSO®MS IR 920** does not contain any purposely added calcium chloride or other chloride based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

### Packaging:

– Pails: 20 L

#### Directions for use: Dosage

between 3 and 10 kg per 100 kg of cement. A 5 % dosage of the product to the weight of cement is commonly used.

**CHRYSO®MS IR 920** can be added to the water before mixing the concrete. However, it can be added to the concrete after mixing. The correct quantity of **CHRYSO®MS IR 920** should be measured using a recommended dispenser.

The optimum dosage of **CHRYSO®MS IR 920** can only be established after trial tests, taking into account local conditions, materials and specification requirements.

Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using outside recommended dosage ranges.

#### Compatibility

**CHRYSO®MS IR 920** is compatible with all types of Portland cement, class C and F fly ash, slag, calcium chloride, fibers and approved air entraining admixtures.

#### **Precaution:**

• Store away from frost. Use CHRYSO®MS IR 920 at a temperature superior to 0°C.

• Should the product freeze, its properties can be recovered after thawing and agitating thoroughly.

• Spillage of CHRYSO®MS IR 920 should be absorbed onto sand earth or vermiculite and disposed through authorised waste management companies. Remnants can be hosed down with large volumes of water.

• Shelf life: 6 months.

#### ■ Safety:

**CHRYSO®MS IR 920** is not considered dangerous to handle. Please refer to the material safety data sheet for additional information.

#### **About CHRYSO:**

Worldwide leader for cement and concrete additives for over 70 years, **CHRYSO** has been designing, producing, specifying and delivering its added-value solutions to the construction professionals with outstanding innovation and quality service. As a result, **CHRYSO**'s brand and products have been associated with the most prestigious and demanding construction projects over the globe.

# Manufactured under License by,



No.17, 5th St., North Falamak Ave., Shahrak Gharb Tel: +98 21 88370130 up to 4 Fax: +98 21 88075715 Zip1467885484 Tehran – Iran E-mail: info@arshiaorang.com

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specialists.